


# AAS7506 SI

## MEETING STILE SEAL

### FITTING GUIDE



#### CONTENTS

- AAS7506 si meeting stile seal
- Screw pack

#### TOOLS REQUIRED

- Tape measure
- Pencil or marker
- Saw (power/hack)
- 2.5mm drill bit and countersink
- Drill
- Screw driver
- Knife
- Router (rebated installation).

## INSTALLATION DETAIL

This product can either be face fixed or rebated.

#### FACE FIXED

It is not necessary to remove the door from its hinges unless otherwise specified.

#### STEP 1

Remove the seal from the packaging and measure the height of the meeting stile.

#### STEP 2

Cut the aluminium carrier to the required length.

#### STEP 3

Cut the semi-rigid Batwing® gasket to the required length.

#### STEP 4

Determine the door handing and position the carrier against the appropriate meeting stile and mark out the hole locations with a pencil. Use the self adhesive tape to help hold the position while fixing.

#### STEP 5

Drill pilot holes with a 2.5mm drill bit (if required).

#### STEP 6

Screw fix the aluminium carrier length to the meeting stile using the screws supplied.

#### STEP 7

Press the semi-rigid Batwing® gasket into the aluminium carrier. There are no fixings here, it is a simple interference fit.

#### STEP 8

Close the door and ensure the seal makes uniform contact with the opposite door leaf.

**We recommend the AAS7506 perimeter seal be fitted with any perimeter seal and drop seal.**



#### IMPORTANT

Ensure that the installation of this product does not impede the opening or closing of the door. It is recommended to check the adjustment of the door seal periodically to ensure the door assembly to which it is fitted, closes & latches properly.

#### DISCLAIMER

Recommendations as to methods, use of materials and construction details are based on the experience and knowledge of Lorient and are given in good faith as a general guide and service to designers, contractors and manufacturers. Lorient reserves the right to make alterations or delete installation detail without prior notice.



ASSA ABLOY LTD T/A LORIENT  
Endeavour House  
Fairfax Road  
Heathfield Ind Estate  
Newton Abbot  
Devon TQ12 6UD  
United Kingdom

+44 (0)1626 834252  
www.lorient.com.au

All rights reserved. No part of this fitting guide may be reproduced, stored in a retrieval system, or transmitted in any means, electronic, mechanical, photocopying, recording or otherwise without the written permission of Lorient.

© 2024 ASSA ABLOY Ltd T/A Lorient. Lorient is a registered trade mark of ASSA ABLOY LIMITED in England.

For more information please call:

**+44 (0)1626 834252**