

LP1004, LP1504, LP2004 FIRE SEAL FITTING GUIDE

certifire

(CF330 & CF341)



CONTENTS

- LP1004, LP1504, or LP2004 fire seal

TOOLS REQUIRED

- Router
- Suitable router bit
- Secateurs

INSTALLATION DETAIL

NOTE

We recommend that, in line with good joinery practice, the edges of door leaves are given a 1° leading edge and chamfered on both edges.

STEP 1

Before fitting the door frame to the opening, rout all grooves to the back of the frame and head.

ROUT SIZES

LP1004: 10 x 4mm

LP1504: 15 x 4mm

LP2004: 20 x 4mm

STEP 2

Repeat the same operation for the inside of frame and doors where applicable.

NOTE

All grooves should be of suitable width and depth such that the seals do not stand proud of their surroundings.

STEP 3

Make sure grooves are free from dust and grease. Lorient does not recommend oil or solvent based paint/primers.

STEP 4

Measure and cut all seals to length using secateurs. Remove self-adhesive backing and butt joint fit all seals to inside and outside of door frame or door, and meeting stiles of pairs of doors where applicable. Pressure must be applied to activate adhesive backing properties.

NOTE

Pinning of seals is not recommended.

IMPORTANT

Application should be at a temperature **NO LESS than 10°C**. Once installed our fire seals may, if required, be painted over.

Freshly painted doorsets should be left open until the paint is fully dry and cured before fire seals are fitted. Some paint or lacquers will affect adhesion.


HANDLING + STORAGE

No special precautions are required when handling Lorient acoustic, smoke and fire seals, but they should always be treated with care and not bent or twisted. Safety data sheets are available on request.

These products do not fall within the scope of COSHH regulations. Lorient intumescent seals should be stored flat in a clean, dust-free area away from heat and at a storage temperature of between 5°C and 40°C (50-80%relative humidity).

SAFE USE + DISPOSAL

To the best of Lorient's knowledge no special arrangements are required. Dispose of inline with local waste guidelines.



NOTE

Recommendations as to methods, use of materials and construction details are based on the experience and knowledge of Lorient and are given in good faith as a general guide and service to designers, contractors and manufacturers.

Lorient reserves the right to make alterations or delete any installation detail without prior notice.

V2

LORIENT
ASSA ABLOY

ASSA ABLOY LTD T/A LORIENT
Endeavour House
Fairfax Road
Heathfield Ind Estate
Newton Abbot
Devon TQ12 6UD
United Kingdom

+44 (0)1626 834252
www.lorientgroup.com

All rights reserved. No part of this fitting guide may be reproduced, stored in a retrieval system, or transmitted in any means, electronic, mechanical, photocopying, recording or otherwise without the written permission of Lorient.

© 2024 ASSA ABLOY Ltd T/A Lorient. Lorient is a registered trade mark of ASSA ABLOY LIMITED in England.

For more information please call:

+44 (0)1626 834252