# LAS4016 THRESHOLD PLATE

## **FITTING GUIDE**



LENGTH

#### **CONTENTS**

- Aluminium threshold
- Stainless steel screws and plugs

#### **TOOLS REQUIRED**

- Tape measure
- · Pencil or marker
- . Saw, hand or power
- Power drill
- 4.5mm drill bit
- 6mm masonry bit

Recommendations as to methods, use of materials and construction details are based on the experience and knowledge of Lorient and are given in good faith as a general guide and service to designers, contractors and manufacturers.

Lorient reserves the right to make alterations or delete any installation detail without prior notice.

### **INSTALLATION DETAIL**

#### NOTE

It is not necessary to remove the door from its hinges.

#### STEP 1

Remove the plate from the packaging and measure the door width, between jambs or door stops to determine plate length required.

#### STEP 2

Measure the threshold plate and mark the desired length (and profile if cutting around the door stop) with a pencil.

#### STEP 3

Cut the threshold plate to the desired length using a saw.

#### STEP 4

Position the plate on the door sill in required location.

#### STEP 5

With the plate in position, mark hole centres on floor. Using masonry drill, create fixing holes. Clean away dust and insert supplied plastic plugs.

#### STEP 6

Screw fix the threshold in place using the screws supplied.

#### NOTE

Where the threshold plate meets the door stop, sealant may be applied to prevent water ingress.

#### STEP 8

Check to ensure the door opens and closes with ease.

#### NOTE

For effective operation, the LAS4016 threshold plate requires a minimum of 12mm clearance between the door and the floor.

Ensure that the installation of this product does not impede the opening or closing of the door.



#### **IMPORTANT**

Ensure that the installation of this product does not impede the opening or closing of the door. It is recommended to check the adjustment of the door seal periodically to ensure the door assembly to which it is fitted, closes & latches properly.

#### DISCLAIMER

Recommendations as to methods, use of materials and construction details are based on the experience and knowledge of Lorient and are given in good faith as a general guide and service to designers, contractors and manufacturers. Lorient reserves the right to make alterations or delete installation detail without prior notice.



ASSA ABLOY LTD T/A LORIENT Endeavour House Fairfax Road Heathfield Ind Estate Newton Abbot Devon TQ12 6UD United Kingdom

> +44 (0)1626 834252 www.lorientgroup.com

All rights reserved. No part of this fitting guide may be reproduced, stored in a retrieval system, or transmitted in any means, electronic, mechanical, photocopying, recording or otherwise without the written permission of Lorient.

 $\ \ \,$  0 2024 ASSA ABLOY Ltd T/A Lorient. Lorient is a registered trade mark of ASSA ABLOY LIMITED in England.