


MEETING STILE SEAL

LAS7006 si

FACE-FIXED

A high performance seal designed for use on plain or rebated meeting stiles. With proven medium temperature smoke performance, it also makes a positive contribution to light, sound, and draught containment. The leg can be cut out to make way for locks and latches.



▲ LAS7006 si



▲ LAS7006 si

SYSTEM SPECIFICATIONS

Test evidence

- ▶ Smoke: BS EN 1634-3:2004 at ambient and medium temperature; effective smoke seal up to 200°C.

Performance

- ▶ Protects against smoke, sound draught, dust, light and weather.

Location

- ▶ Meeting stiles of single swing doors.
- ▶ Double doors – where only one door leaf is in use or a door selector is fitted.

Use with

- ▶ Practically any perimeter seal.

Seal material

- ▶ Aluminium carrier with flexible silicone blade.

Standard length

- ▶ 2.1m.

Fixing

- ▶ Secure with heavy duty self-adhesive tape.
- ▶ Screw into place (fixings supplied).
- ▶ Note: A door selector should be considered unless one leaf is intended to be fixed.

Finishes

- ▶ Silver anodised aluminium with grey silicone rubber gasket as standard.
- ▶ Other finishes available to special order (non-standard – charges and lead times apply).