LVHCTD + LVH44/LVH54

CASSETTE TYPE DAMPER

Lorient's Cassette Type Damper allows simple and rapid duct installation in small spaces, along with excellent access during commissioning and servicing. When used with an LVH44 or LVH54 air transfer grille can provide up to 240 minutes fire and smoke resistance.










Key benefits

- ► Sliding cold smoke shutter module allows easy access for servicing
- ► Easy installation of air transfer grille into fire compartment boundary
- ► Shutter plates tolerate a pressure differential of 300Pa
- ▶ Low cold smoke leakage rates
- May be used purely as a cold smoke damper by excluding the air transfer grille
- ► Can incorporate either LVH44 or LVH54 air transfer grilles
- Controlled by 'Talkback' system providing status information + auto-cycling.



LVHCTD Shown with LVH54

STANDARD SIZES AVAILABLE (MM)

WIDTH 200 200 250 250 300 300 300 350 400 400 400 450 450 450 600 600 600 HEIGHT 150 200 200 250 150 200 250 300 250 150 250 300 250 300 450 150 250 300

Other non-standard sizes may be available - please ask for details.

SYSTEM SPECIFICATIONS

Performance

- ▶ Inclusion of LVH44 air transfer grille will provide up to 120 minutes fire resistance.
- Inclusion of LVH54 air transfer grille will provide up to 240 minutes fire resistance and 30 minutes insulation.

Size

- ▶ Width: 200mm 600mm (in 50mm increments).
- ▶ Height: 150mm 300mm (in 50mm increments).
- ▶ Square and rectangle options available.

Thickness

▶ Depth: Subject to application.

Free area

Approx 40% free area.

Application

▶ Suitable for ducts.

Materia

- Manufactured using welded galvanised steel sheet with the smoke shutter plate location formed by galvanised steel spacer strips.
- Intumescent fire seal strip prevents hot gas leakage.
- Shutter plate assembly is produced from 3 sheets of fire resistant glass reinforced plastic of low toxicity.
- Actuator motor and circuit board are protected within a removable galvanised steel enclosure.

Use with

- ▶ Talkback damper control system.
- LVH44 or LVH54 air transfer grilles (optional).

Specification

