Planet KG-S Narrow



FACE-FIXED














A slimline, face-fixed automatic drop seal designed for glass, timber, metal, and PVC doors. Its ultra-narrow 11.5mm profile makes it ideal for minimalistic applications. Featuring a high-efficiency mechanism with a single-sided trigger, it enables parallel lowering and automatic compensation for sloping floors. Suitable for fire and smoke-shielding doors, with a seal height of up to 16mm. Designed for adhesive mounting. An optional bevel lip is available for uneven floors, accommodating gaps of up to 20mm.





Planet KG-S Narrow



Planet KG-S Narrow Drop Seal

SYSTEM SPECIFICATIONS

Key benefits

- For new and existing doors.
- ▶ Unilateral and silent actuation.
- No scraping / trailing on the floor, thanks to parallel drop.
- ▶ High-quality silicone lip, lateral protrusion adjustable.
- ➤ Can be shortened to the next smaller stock length.

Characteristics

- Suitable for use on glass, timber, metal & PVC doors.
- Sound absorption level up to 48dB (at ground air 7 mm).

Possible door types (depending on options)

Single swing doors, double swing doors, sliding doors.

Profile size

▶ 11.5mm x 38mm.

Max drop height

▶ 16mm.

Profile material

Aluminium.

Seal material

- Planet KG-S narrow RD: High-quality silicone.
- Planet KG-S narrow FH+RD: High-quality self-extinguishing silicone with aluminium carrier
- Bevel lip available for uneven floors (Left-handed or right-handed variants.

Adjustment

- > Self-levelling on uneven surfaces.
- Automatic compensation of sloped floors.
- ▶ Easy drop height adjustment.
- Door bottom can be adjusted without seal removal.

Drop height adjustment

▶ Using 3mm allen key.

Standard lengths

- 459mm, 584mm, 709mm, 834mm, 959mm, 1084mm, 1209mm, 1334mm, 1459mm.
- Note: Each length can be cut back by 125mm.
- Sizes up to 6m are available to special order.

Fixing

• Glued to the side with VHB adhesive tape or silicon or UV.

Accessories (supplied)

Planet stopping plate, type 1 (stainless steel) and cover plate.

Finishe

- Silver anodised EV1 as standard.
- Matt anodised stainless steel (INOX) or black C35 matt anodised or special colours powder coated (RAL / DB / NCS) to special order.

