
Planet X3

MORTISED



A mortised automatic drop seal designed for exterior doors made of timber, metal, or PVC. Engineered for high-performance weather protection, it is driving rain-proof (7A/9A, ift certified) without requiring a drainage channel. Featuring a high-efficiency mechanism with hinge-side triggering, it provides three sealing movements—downwards, to the left, and to the right—each individually adjustable. Drop height adjustable between 5–12mm, with a side lift of 2–6mm. Durable silicone lip for reliable sealing.



Planet X3 Drop Seal

SYSTEM SPECIFICATIONS

Key benefits

- High-quality silicone gasket.
- > Three sealing movements simultaneously.
- Barrier free.
- Can be shortened to the next smaller stock length.

Characteristics

- Suitable for use on metal, timber & PVC doors.
- Driving rain proof (7A/9A, ift certified), no drainage channel required.
- Sound absorption level up to 50dB (at ground air 7 mm).

Possible door types (depending on options)

- Single swing doors, double swing doors, sliding doors, folding doors.
- Minimum door thickness 68mm.

Profile size

> 22mm x 30mm.

Groove size

22.5mm wide x 30-32mm deep.

Max drop

- 5-12mm (height).
- 2-6mm (side lift).
- Profile material
- Aluminium.

Seal material

High-quality silicone.

Adjustment

- Self-levelling on uneven surfaces.
- Automatic compensation of sloped floors.
- Easy drop height & side adjustment.
- Door bottom can be adjusted without seal removal.

Drop height adjustment

 Using 3mm allen key for side lift adjustment (2-6mm). Front side adjustment with 4mm allen key.

Planet X3



Standard lengths

- 835mm, 960mm, 1085mm, 1210mm, 1335mm, 1460mm.
- Note: Each length can be cut back by 125mm.
- Sizes up to 6m are available to special order.

Fixing

• Fixing with mounting bracket and self-tapping screws on the side.

Accessories (supplied)

 Planet assembly set X3 for wooden doors with 2 mounting brackets (stainless steel), 4 screws, version Planet X3 shortenable: incl. Planet shortening set X3 with quick clamping system

Finishes

Silver as standard.

T: +44 (0)1626 834252 E: mktg@lorientuk.com www.lorientuk.com



LORIENT